

LOW VOLTAGE AND HIGH VOLTAGE TECHNICAL SPECIFICATION

Electrical

Input voltage: Low Voltage = 110-127 V, High Voltage = 208-240 V

Frequency: Low Voltage = 50 or 60 Hz, subject to voltage (85-115 V at 50 Hz; 85-130 V at 60 Hz); High Voltage = 50 & 60 Hz

Rated power: 1400 W

Motor type: Dyson digital motor – V4 brushless DC Motor

Motor switching rate: 6,100 per second

Motor speed: 92,000 rpm

Amp: Recommended dedicated 15 amp circuit, Low voltage = 11.7 amps at 120V, High voltage = 7.3 amps

Operating temperature range: 32° – 104°F

Heater type: None

Standby power consumption: Less than 0.5 W

Construction

Tap construction: Stainless steel (brushed)

Lead Free

Under counter motor bucket: Molded ABS (main unit) also uses polycarbonate and polypropylene

Exterior screw type: Torx T15

Water ingress protection rating to IP35

Filter

Double-life HEPA filter (glass fiber and fleece prelayer)

Bacteria removal 99.97% at 0.3 microns

Operation

Touch-free infra-red activation

Hand dry time measurement: 14 seconds*

Operation lock-out period: 30 seconds

Airspeed at apertures: 420 mph

Maximum Altitude: 2,000m/6,561 ft.

Operating airflow: Up to 7.92 gal/sec and 63.5 CFM

Rated operating noise power: 85 db(A)

Water operation

Water flow rate: 1.06 gal/min

Tap Aerator: 0.5 gal/min aerator outlet (Note: Optional .35 gal/min multi spray laminar aerator available as a service part)

Tap power supply: Mains supply

Water temperature control: Thermostatic mixer recommended (not supplied)

Water pressure required: 14.5-116 psi

Logistics

Serial number prefix: AB11 AN7

Net weight: AB11 19.7 lbs.

Packaged weight: AB11 25.9 lbs.

Packaged dimensions: AB11 (H) 11-7/8" x (W) 24: x (D) 14-3/4"

UPC barcodes: AB11: 885609001487 (Low Voltage)
885609004426 (High Voltage)

Standard guarantee

5 year parts and 5 year limited labor warranty



Product range (Select one)

AB11 Wall

Part number/SKU

- Low Voltage: 301850-01
- High Voltage: 301843-01



Sink specifications

The Dyson Airblade™ Tap is compatible with most sink types. Ensure plugs are not installed in the sinks. See the Tap Pre-Installation Guide for more details.

Sink dimensions: All sink measurements are internal unless stated otherwise. Sink width – Min.: 13¾", Front to back – Min.: 11¾"; Sink depth – Min. 4"

Sink materials: Sinks with highly polished surfaces should be avoided e.g. shiny chrome. Porcelain or brushed metal are ideal.

Accreditations

Carbon Trust

HACCP International

NSF International

AB11 is ADA compliant

Contributes to LEED certification



The Carbon Reduction Label is the registered trade mark of the Carbon Trust. HACCP International non-food certification mark is the registered trademark of HACCP International. HACCP International have certified Dyson products based on their recommended installation and operating conditions. The NSF logo is the registered trade mark of NSF International.

*Dry time measured using Dyson test method 769 based on NSF P335 using a measurement of 0.1g residual moisture.

For more information, please contact Allied Hand Dryer
1-800-535-4393 / www.handdryer.com / sales@handdryer.com


dyson airblade tap

TECHNICAL SPECIFICATION

AB
11



FRONT ELEVATION



Tap dimensions

AB11 Length 12¹/₁₆" Width 11⁵/₈"

Motor bucket dimensions

AB11 Height 10³/₄" Width 5⁵/₁₆" Depth 7⁷/₁₆"

All dimensions shown in inches (+/- ³/₁₆ inches)

For more information, please contact Allied Hand Dryer:
1-800-535-4393
www.handdryer.com
sales@handdryer.com